

输液泵锂电池

型号: Li-ion 18650 2200mAh 14.8V (4 串 1 并组合)

电压范围: **12V-16.8V** 成品电池内阻: ≤**350**mΩ

电池组尺寸: MAX 37*37*67mm

最大放电电流: >3A (可根据客户要求把电流放大或减小) 瞬间放电电流: >6A (可根据客户要求把电流放大或减小)

最大充电电流: >0.2-0.5C(可根据客户要求把电流放大或减小)

工作温度: 充电: 0~45℃

放电: -20~60℃

引线及插头型号:根据客户的要求订做 保护板参数:根据客户的產品订做



Model No: Li-ion 18650 2200mAh 14.8V (4S1P)

Voltage range:: 12V-16.8V internal resistance≤350mΩ Battery size: MAX 37*37*67mm

Maximum discharge current: > 3A (according to customer requirements to current amplification or reduction)

Discharge current moment: > 6A (according to customer requirements to current amplification or reduction)

Maximum charging current: > 0.2-0.5C (according to customer requirements to current amplification or reduction)

Working temperature: : charging : $0\sim45$ $^{\circ}\mathrm{C}$

Discharge: -20~60 °C

Charge and discharge times: > 500 times

Lead and plug type: customized according to customer requirements Protection parameters: according to customers customized products





Website builder: Sunher New Media